

# MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA'S Hazard Communication Standard.

29 CFR 1910. 1200. Standard must be consulted for specific requirements.

Identify (As Used on Label and List) : AR OIL

## Section I

<u>Manufacturer &amp; Distributor Name and Address:</u> MFG : J.MORITA MFG. CORP. 680 Higashihama Minami-cho, Fushimi-ku, Kyoto, 612 JAPAN DIST : J.MORITA USA, INC. 14712 Bentley Circle, Tustin CA 92780, U.S.A.	Emergency Telephone Number : 714-514-2854
	Date Prepared : 1998, Sep. 30

## Section II Hazardous Ingredients / Identity Information

Hazardous Components :	C.A.S.No.	OSHA PEL	ACGIH TLV
Liquid Paraffin	8042-47-5	N / A	N / A

## Section III Physical / Chemical Characteristics

Boiling Point : 350°C Vapor Pressure : 0.01mmHg(at 20°C) Solubility in Water : Slightly Soluble Appearance and Color : Colorless, Liquid	Specific Gravity : 0.87g/cm <sup>3</sup> (at -15°C) Melting Point : -17.5°C Evaporation Rate : 0
---	--

## Section IV Fire and Explosion Hazardous Data

Flash Point : 256°C	Flammable Limit	LEL : 7%	UEL : 0.9%
Extinguishing Media : CO <sub>2</sub> , Form, Drychemical, Powder-Class A-O Special Fire Fighting Procedures : Do not spray water on the fire; use a fire extinguisher or other chemicals, materials etc. specifically designed for extinguishing fires. Unusual Fire and Explosion Hazards : Dangerous when exposed to high heat or flames.			

## Section V Reactivity Data

Stability	Unstable		Condition to Avoid : High heat or Flame.
	Stable	×	
Incompatibility (Materials to Avoid) : Strong Oxidizer (Chlorine, Flourine, Bromine)			
Hazardous Decomposition or Byproducts : None			
Hazardous Polymerization	May Occur		
	Will Not Occur	×	

ABBREVIATIONS : N / E - Not Established      N / A - Not applicable

